



Stormtite[®]

SYNTHETIC UNDERLAYMENT



Use synthetic underlayment directly on sloped roof decks, under asphalt shingles.

Stormtite®

SYNTHETIC UNDERLAYMENT



PRODUCT SPECIFICATIONS

Length	250 ft (76.2 m)
Width	48" (1,219 mm)
Roll Contents	1000 sq ft (92.9 m ²)

ASTM E108/UL790 and CAN/ULC S107 Class A Fire Resistance.*

*Note: All values shown are approximate.
When installed under Class A fire rated asphalt shingles and over 3/8 in (9.5 mm) minimum thickness APA-labeled exterior grade plywood or OSB deck.

PROFORMAX™

INTEGRATED ROOFING ACCESSORIES

Shingles alone are usually not enough to protect your home. IKO has developed superior multilayered roofing components incorporating our industry-leading products. A complete roofing system ensures your roof's optimum performance.

- 1 DECK PROTECTION.** IKO StormShield® Ice & Water Protectors and IKO GoldSeam™ Roof Sealing Tape.
- 2 SYNTHETIC UNDERLAYMENT.** Stormtite®.
- 3 ROOF STARTERS.** Leading Edge Plus™ or EdgeSeal®.
- 4 CAPPING SHINGLES.** Hip & Ridge 12™/Hip & Ridge Class 4™ or IKO UltraHP®/IKO UltraHP® IR.

Synthetic underlayment that will totally rock the way you roll.

IKO Stormtite® synthetic underlayment is engineered to be used under asphalt shingles. It qualifies as an IKO PROFORMAX Integrated Roofing Accessory and is covered by a limited 15-year material warranty.

Here's why it rocks.

- ✔ Stronger than felt. **Stormtite** is more resistant to tearing and shredding when installers walk on it. Plus it's coated top and bottom with tough polyolefin for superior weather resistance.
- ✔ More flexible, even in cold weather. **Stormtite** is easy to install around vents, dormers, skylights and other typical roof structures. It lays flat without curling and is super durable.
- ✔ Synthetic, non-breathable material. **Stormtite** effectively sheds water that gets behind shingles and it's engineered to be a vapor-retarder.
- ✔ Lighter than felt. A single roll of **Stormtite** contains 1000 square feet.
- ✔ Each roll is printed with dashed lines and bold dots at the recommended fastener areas for easier and improved application.

Ready to Roll with Stormtite?



© Copyright 12/23 - MR9L083

Find out more about our products now by talking to an IKO Sales Representative or your professional roofing contractor or contact us directly at: **United States 1-888-IKO-ROOF (1-888-456-7663), Canada 1-855-IKO-ROOF (1-855-456-7663).** Or visit our website at: **IKO.COM.**

Note: The information in this document is subject to change without notice. IKO assumes no responsibility for errors that may appear in this document.



APPLICATION INSTRUCTIONS